

AquaSParkle

DiOx Ultra



Key Features

- Powerful cleaner for hot tubs and swimming pools
- Aids biofilm removal

Warm hot tub and swimming pool water can provide the ideal breeding ground for bacterial growth. As bacteria starts to form on surfaces and in hot tub pipework, biofilm can begin to form. Biofilm is extremely resistant to chlorine. AquaSParkle DiOx Ultra will effectively clean hot tub and swimming pool pipework and surfaces.

Hot Tub Application Instructions

1. Isolate your chlorine, redox & pH probes from the hot tub or pool water.
2. Isolate any chlorine or bromine feeder prior to product application.
3. For systems with a cartridge filter, remove & clean the cartridge, then return to service before treatment starts.
4. **CAUTION:** Do not use the hot tub or pool during DiOx Ultra treatment.
5. Refer to table below for number of tablets required for treatment.
6. Wear suitable protective gloves & eye protection when handling product.
7. Open the sachet(s) and carefully drop the required number of tablets around the hot tub or pool perimeter with the pump(s) running.
8. After 15 – 20 minutes, backwash your filter. The hot tub or pool will be safe to use after 8 hours or immediately if draining and refilling with fresh water (assuming sanitiser & pH levels are correct).

Dose Rates					
Water Volumes		Number of tablets			
Litres	Gallons	Public Pool	Public Spa	Private Pool	Private Spa
1,000	220		2		1
2,000	440		4		2
50,000	11,000	16		8	
100,000	22,000	32		16	

Other Applications

To clean a biofilm covered surface such as floatation aids, covers, channel grates or around the pool side and in changing areas, use the following dose rate:

1. Add one tablet to 20ltr of water (using a clean bucket) and allow the tablet to fully dissolve.
2. Apply the solution to the surface to be cleaned, leave for 5 minutes and then wash off with clean water.

