

Revision: 11 Mar 2015

SAFETY DATA SHEET

SECTION 1 Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

- Product Name: Pipe and Fitting Cleaner
- Product Part Number: 108
- Contains butanone

1.2 Relevant identified uses of the substance or mixture and uses advised against

- Use of the substance/mixture: Pipe Cleaner, Thinner
- Use advised against: No information available

1.3 Details of the supplier of the safety data sheet

- Name of Supplier: Plastica Ltd
- Address of Supplier: Perimeter House
Napier Road
St Leonards-on-Sea
East Sussex
United Kingdom
TN38 9NY
- Telephone: +44 (0) 1424 857857
- Email: Info@plasticapools.com

1.4 Emergency telephone number

- Emergency Telephone: 0800 043 0892

SECTION 2 Hazards identification

2.1 Classification of the substance or mixture

- Classification (REGULATION (EC) No 1272/2008) [CLP/GHS]: Flam. Liq. 2, H225, Eye Irrit. 2, H319, STOT SE 3, H336, EUH066
- Classification (67/548/EEC, 1999/45/EC) [CHIP]: F; R11, Xi; R36, R66, R67
- Additional information: For full text of R-phrases and Hazard- and EU Hazard-statements: see section 16

2.2 Label elements



GHS02



GHS07

- Signal Word: Danger
- Symbols: GHS02, GHS07
- Hazard phrases
Highly flammable liquid and vapour.
Causes serious eye irritation.
May cause drowsiness or dizziness.
- Precautionary Phrases
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.

Revision: 11 Mar 2015

SECTION 2 Hazards identification (....)

If eye irritation persists: Get medical advice/attention.
Store in a well-ventilated place. Keep container tightly closed.
Dispose of contents/container in accordance with
local/regional/national/international regulations.

Supplemental Hazard Information (EU)
Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards

- Vapours are heavier than air and may travel considerable distances to a source of ignition and flashback
-

SECTION 3 Composition/information on ingredients**3.1 Substances****3.2 Mixtures**

- butanone; ethyl methyl ketone
Concentration: 60-100%
CAS Number: 78-93-3
EC Number: 201-159-0
Categories: Flam. Liq. 2, Eye Irrit. 2, STOT SE 3
R/H Phrases: H225,H319,H336, EUH066, R11,R36,R66,R67
Symbols: GHS02,GHS07, F, Xi
REACH Registration Number: 01-2119457290-43-XXXX
Substance with a Community workplace exposure limit, see Section 8
-

SECTION 4 First aid measures**4.1 Description of first aid measures**

- Contact with skin
Remove contaminated clothing immediately and drench affected skin with plenty of water.
Then wash with soap and water
If skin irritation occurs: Get medical advice/attention.
- Contact with eyes
If substance has got into eyes, immediately wash out with plenty of water for at least 15 minutes
Irrigate eyes thoroughly whilst lifting eyelids
If eye irritation persists: Get medical advice/attention.
- Ingestion
Rinse mouth with water (do not swallow)
Do not induce vomiting
Get immediate medical advice/attention.
- Inhalation
Remove victim to fresh air and keep at rest in a position comfortable for breathing.
When in doubt or symptoms persist, seek medical attention

4.2 Most important symptoms and effects, both acute and delayed

- May cause irritation to skin, eyes and the respiratory tract.
 - May cause drowsiness
-

Revision: 11 Mar 2015

SECTION 4 First aid measures (....)

- May cause dizziness
- May cause dermatitis

4.3 Indication of any immediate medical attention and special treatment needed

- Treat symptomatically
-

SECTION 5 Fire-fighting measures

5.1 Extinguishing media

- In case of fire: use alcohol resistant foam or dry agent for extinction

5.2 Special hazards arising from the substance or mixture

- Highly flammable liquid and vapour.
- Vapours are heavier than air and may travel considerable distances to a source of ignition and flashback
- In a fire or if heated, a pressure increase will occur and the container may burst
- Gives off irritating or toxic fumes (or gases) in a fire.
- Decomposition products may include carbon oxides

5.3 Advice for firefighters

- Keep container(s) exposed to fire cool, by spraying with water
 - Special protective equipment: Wear self-contained breathing apparatus (SCBA). Wear full protective clothing including chemical protection suit.
 - Collect contaminated fire extinguishing water separately. This **MUST** not be discharged into drains. Prevent fire extinguishing water from contaminating surface or ground water.
-

SECTION 6 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- Ensure adequate ventilation
- Avoid breathing dust/fume/gas/mist/vapours/spray.
- Avoid contact with skin and eyes.
- Wash thoroughly after dealing with spillage
- Eyewash bottles should be available

6.2 Environmental Precautions

- Avoid release to the environment.
- Do not allow to enter public sewers and watercourses
- If contamination of drainage systems or water courses is unavoidable, immediately inform appropriate authorities

6.3 Methods and material for containment and cleaning up

- Ventilate area
- Eliminate all ignition sources if safe to do so.
- Absorb spillage in earth or sand
- Remove contaminated material to safe location for subsequent disposal
- Place in appropriate container
- Seal containers and label them
- Ventilate the area and wash spill site after material pick-up is complete

6.4 Reference to other sections

- Wear protective clothing as per section 8
-

SECTION 7 Handling and storage

7.1 Precautions for safe handling

Revision: 11 Mar 2015

SECTION 7 Handling and storage (....)

- Ensure adequate ventilation
- Avoid breathing vapours, mist or gas
- Do not get in eyes, on skin, or on clothing.
- Contaminated work clothing should not be allowed out of the workplace.
- Do not eat, drink or smoke when using this product.
- Keep away from heat and sources of ignition
- Eyewash bottles should be available
- Wash thoroughly after handling.

7.2 Conditions for safe storage, including any incompatibilities

- Keep in highly flammable materials store
- Store away from other materials.
- Keep away from food, drink and animal feedingstuffs
- Keep container tightly closed, in a cool, well ventilated place
- Ground/bond container and receiving equipment.
- Take precautionary measures against static discharge.
- Keep away from oxidisers, heat, flames or ignition sources
- Protect from sunlight.
- Keep away from combustible material

7.3 Specific end use(s)

- Pipe Cleaner

SECTION 8 Exposure controls/personal protection

8.1 Control parameters

- butanone; ethyl methyl ketone
 - WEL (long term) 600 mg/m³ (UK)
 - WEL (long term) 200 ppm (UK)
 - WEL (short term) 899 mg/m³ (UK)
 - WEL (short term) 300 ppm (UK)
 - Can be absorbed through skin

8.2 Exposure controls

- Do not eat, drink or smoke when using this product.
- Engineering controls should be provided which maintain airborne concentrations below the relevant guidelines
- In case of insufficient ventilation, wear suitable respiratory equipment
- Wear suitable filtering half mask respirator approved to standard EN 149
- Wear suitable protective clothing, including eye/face protection and gloves (nitrile are recommended)
- The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and standard EN 374.
- The selection of a suitable glove depends on work conditions and whether the product is present on its own or in combination with other substances. Breakthrough time is dependent on the characteristics of the brand of glove used and the supplier should be consulted.
- Wear safety glasses approved to standard EN 166.
- When handling this substance, e.g. sampling, wear goggles giving complete eye protection
- Eyewash bottles should be available



Goggles



Gloves



Respirator



No Smoking

SECTION 9 Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Appearance: Liquid, viscous, clear
- Odour: Ketone
- pH: No information available
- Boiling Point/Range: 79-80°C
- Vapour Density: No information available
- Vapour Pressure: 105 hPa @ 20°C
- Melting point/Range: -86°C
- Freezing point/Range: No information available.
- Viscosity: Viscous
- Relative Density: 0.806 @ 25°C
- Flashpoint: -5°C
- Evaporation Rate: No information available
- Solubility in water: Miscible
- Solubility in Fat: No information available
- Partition Coefficient (n-Octanol/Water): Log Kow 0.29
- Explosive Properties: Lower explosive limit 1.5 % (in air), Upper explosive limit 11.5 % (in air)
- Oxidising Properties: No information available

9.2 Other information

- No information available
-

SECTION 10 Stability and reactivity

10.1 Reactivity

- May decompose on exposure to organic peroxides

10.2 Chemical stability

- No decomposition if stored normally.

10.3 Possibility of hazardous reactions

- May form explosive vapour/air mixtures

10.4 Conditions to avoid

- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.

10.5 Incompatible materials

- Incompatible with oxidizing substances
- Incompatible with acid
- Incompatible with peroxides

10.6 Hazardous Decomposition Products

- Decomposition products may include toxic and irritant fumes
 - Decomposition products may include carbon oxides
-

SECTION 11 Toxicological information

11.1 Information on toxicological effects

Acute Toxicity

- LD50 (oral, rat) (butanone) 2740 g/kg
-

Revision: 11 Mar 2015

SECTION 11 Toxicological information (....)

- LD50 (dermal,rabbit) (butanone) 6480 mg/kg
 - Based on available data, the classification criteria are not met
 - Skin corrosion/irritation
 - Based on available data, the classification criteria are not met
 - Serious eye damage/irritation
 - Causes serious eye irritation.
 - Classification based on calculation and concentration thresholds
 - Respiratory or skin sensitisation
 - No information available
 - Germ cell mutagenicity
 - No information available
 - Carcinogenicity
 - No information available
 - Reproductive toxicity
 - No information available
 - Specific target organ toxicity (STOT) - single exposure
 - May cause drowsiness or dizziness.
 - Classification based on calculation and concentration thresholds
 - Specific target organ toxicity (STOT) - repeated exposure
 - No information available
 - Aspiration hazard
 - The ingestion of significant quantities may cause damage to lungs
 - Contact with eyes
 - May cause redness and irritation
 - Contact with skin
 - Mildly irritating to skin
 - Prolonged skin contact will result in defatting of the skin, leading to irritation, and in some cases, dermatitis
 - Repeated exposure may cause skin dryness or cracking.
 - Inhalation
 - May cause coughing
 - May cause dizziness, confusion, headache or stupor
 - May cause drowsiness
 - Ingestion
 - May cause gastro-intestinal disturbances
 - The ingestion of significant quantities may cause chronic pneumonitis
-

SECTION 12 Ecological information

12.1 Toxicity

- LC50 (fish) (butanone) 3220 mg/l (96 hr)
- EC50 (crustaceans) (butanone) 5090 mg/l (48 hr)

12.2 Persistence and degradability

- No information available

12.3 Bioaccumulation Potential

- No information available

12.4 Mobility in soil

- Do not allow to penetrate the ground/soil.

12.5 Results of PBT and vPvB assessment

- No information available

12.6 Other Adverse Effects

Revision: 11 Mar 2015

SECTION 12 Ecological information (....)

- No information available
-

SECTION 13 Disposal considerations

13.1 Waste treatment methods

- Disposal should be in accordance with local, state or national legislation
- Do not discharge into drains or the environment, dispose to an authorised waste collection point
- To be disposed of as hazardous waste
- Empty containers may contain flammable vapours

13.2 Classification

- Waste Codes in accordance with the European Waste catalogue (EWC) are origin-defined. Since this product is used in several industries, no Waste Code can be provided by the supplier. The Waste Code should be determined in arrangement with your waste disposal partner or the responsible authority.
 - The waste must be identified according to the List of Wastes (2000/532/EC)
-

SECTION 14 Transport information

Flammable Liquid

14.1 UN Number

- UN No.: 1193

14.2 UN Proper Shipping Name

- Proper Shipping Name: ETHYL METHYL KETONE (METHYL ETHYL KETONE)

14.3 Transport hazard class(es)

- Hazard Class: 3

14.4 Packing group

- Packing Group: II

14.5 Environmental hazards

- No information available

14.6 Special precautions for user

- No information available

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code

- Not applicable

14.8 Road/Rail (ADR/RID)

- Proper Shipping Name: ETHYL METHYL KETONE (METHYL ETHYL KETONE)
- ADR UN No.: 1193
- ADR Hazard Class: 3
- ADR Packing Group: II
- Tunnel Code: D/E

14.9 Sea (IMDG)

- Proper Shipping Name: ETHYL METHYL KETONE (METHYL ETHYL KETONE)
- IMDG UN No.: 1193

Revision: 11 Mar 2015

SECTION 14 Transport information (....)

- IMDG Hazard Class: 3
- IMDG Pack Group.: II

14.10 Air (ICAO/IATA)

- Proper Shipping Name: ETHYL METHYL KETONE (METHYL ETHYL KETONE)
 - ICAO UN No.: 1193
 - ICAO Hazard Class: 3
 - ICAO Packing Group: II
-

SECTION 15 Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- This Safety Data Sheet is provided in compliance with the EC Directive 1907/2006-453/2010
- The Hazardous Waste (England and Wales) Regulations 2005 apply in the UK

15.2 Chemical Safety Assessment

- No information available
-

SECTION 16 Other information

Text not given with phrase codes where they are used elsewhere in this safety data sheet:- EUH066: Repeated exposure may cause skin dryness or cracking. H225: Highly flammable liquid and vapour. H319: Causes serious eye irritation. H336: May cause drowsiness or dizziness. R11: Highly Flammable. R36: Irritating to eyes. R66: Repeated exposure may cause skin dryness or cracking. R67: Vapours may cause drowsiness and dizziness.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of PLASTICA'S limited knowledge and belief, accurate, and reliable as of the date of authorisation of this safety data sheet. However, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the user's responsibility to be satisfied as to the suitability and completeness of such information for the product as used.

Version 1.0