

## Technical data

Model		CDP 40	CDP 40T	CDP 50	CDP 50T	CDP 70	CDP 70T
- Operating range, humidity	%RH	40-100	40-100	40-100	40-100	40-100	40-100
- Operating range, temperature	°C	10-36	10-36	10-36	10-36	10-36	10-36
- Air volume at max. external pressure	m <sup>3</sup> /h	400	400	680	680	900	900
- Capacity at 28°C - RH 60	l/day	34	34	52	52	69	69
- SEC 28°C - RH 60	kWh/l	0,47	0,47	0,48	0,48	0,43	0,43
- Power supply	V/Hz	1 × 230/50	1 × 230/50	1 × 230/50	1 × 230/50	1 × 230/50	1 × 230/50
- Max. power consumption	kW	0.9	0.9	1.5	1.5	1.8	1.8
- Max Ampere consumption	A	3,8	3,8	6,6	6,6	8	8
- Refrigerant	-	R407C					
- Quantity of refrigerant,	kg	0.7	0.7	0.9	0.9	1.2	1.2
- GWP (Global Warming Potential)	-	1774					
- Noise level* (1 m from unit)	dB(A)	46	43	47	44	50	47
- Weight,	kg	56,5	57,5	65,0	66	75,5	77,5
Filter Type		PPI 15					